

HWS-0109P-58 PoE Switch



Key Features

- Ports 1 to 8 support IEEE 802.3af/IEEE 802.3at standard.
- Ports 1-2 of HWS-0109P-58 are default high-priority ports.
- When the switch is in EXTEND mode and the data rate is 10 Mbps, ports 1 to 8 support long-distance data transmission up to 250 meters.
- All ports support 6 kV lightning protection.
- This switch supports Auto MDI/MDIX.
- This switch supports store-and-forward.
- This switch supports MAC address auto learning and auto aging.
- This switch supports smart cache optimization.
- This switch supports desktop / wall mounting.



Specifications

| | |
|--------------------------------------|---|
| Model | HWS-0109P-58 |
| Port | |
| Port amount | 9 |
| Port type | RJ45, 10/100 Base-T(X) |
| Standard | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af/at |
| Forwarding method | Store-and-forward |
| Flow control | Back-pressure flow control in IEEE 802.3x full duplex |
| Priority queue | 2 |
| MAC address table | 4 K |
| QoS | Supported on ports 1 and 2 |
| Switching capacity | 1.8 Gbps |
| Packet forwarding rate | 1.34 Mpps |
| Physical appearance/structure | |
| Appearance | 0.6 mm sheet of galvanized metal without electric fan |
| Weight | 1.77 kg |
| Dimension | 177.5 mm × 104 mm × 26 mm |
| Mounting type | Desktop / wall mounting |
| Environment | |
| Operating temperature | (0 - 40) °C |
| Storage temperature | (-40 - 70) °C |
| Operating humidity | (10 - 90) % RH, non-condensing |
| Storage humidity | (5 - 90) % RH, non-condensing |
| Power supply | |
| Power input | 51 V DC, 1.25 A |
| Reverse connection protection | Supported |
| PoE output power | 58 W |
| Power consumption | < 63 W |
| Other parameters | |
| LED indicator | Link/Act LED indicators, PoE LED indicator, Power LED indicator, 100M LED indicator |

Available Models

| Model | Description |
|--------------|---------------------|
| HWS-0109P-58 | 100 Mbps PoE Switch |

Dimension



Accessory

/

Distributed by



HIKVISION[®]
HiWatch Series

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
050520170918

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com