

DS-KH8350-WTE1

Network Indoor Station

HIKVISION[®]



Key Feature

- Reddot award 2017 winner, 7-inch Touch-Screen Indoor Station
- Wi-Fi, standard PoE/ 12 VDC
- TF card, max 128 G, for capture while video calling
- 8-ch alarm input , 2 alarm output, 1 × RS-485
- Remote unlocking via the client or the APP
- Views live videos of door stations and external cameras

Specification

Display parameters	
Size	7-inch
Operation method	Capacitive touch screen, physical button
Type	Colorful IPS LCD
Video parameters	
Lens	Not supported.
FOV	/
Pixel	/
Audio parameters	
Audio compression standard	G.711 U
Audio Input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio compression bitrate	64 Kbps
Audio quality	Noise suppression and echo cancellation

Volume adjustment	Adjustable
Network parameters	
Communication protocol	TCP/IP, SIP, RTSP
Wired network	10/100 Mbps self-adaptive
Wi-Fi	Wi-Fi 802.11 b/g/n
Bluetooth	/
Zigbee	/
Device interfaces	
Network interface	1 RJ-45 10/100 Mbps self-adaptive
Power interface	1
General	
Power supply	IEEE802.3af, standard PoE 12 VDC/1 A
Power consumption	≤ 7 W
Working temperature	-10 ° C to 55 ° C (14 ° F to 131 ° F)
Working humidity	10% to 90%
Button	1
Installation	Surface mounting
Indicator	0
Weight	With package: 899 g Without package: 355 g
Protective level	/
Dimensions	180 mm × 140 mm × 22.4 mm (7.09" × 5.51" × 0.88")

Battery	/
Application environment	Indoor
Language	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian, Greek, Portuguese, Slovak

Available Model

DS-KH8350-WTE1

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

